

Septic Blaster

Cleaning Waste Water Drip Septic Blaster



Rich, Nutrient Solution & Warmth = Blockage

Blockage Usually Light, Non-Compacted

Low Dosage, Low Cost, Easier to Remove

Application:

Septic Systems & Laterals:

For Septic Tanks, add 20-30 lbs. of Septic Blaster Powder directly to the tank. Mix if possible. For septic laterals, mix 2 lbs. Septic Blaster Powder per gallon of water and inject into laterals using pump and garden hose. Repeat if necessary.

Drip Systems:

Add 5-10 lbs. of Septic Blaster Powder to the distribution box. Mix in the box (use sump pump or manually mix) and move the liquified Septic Blaster Powder to the field. Alternatively, mix 2 lbs. of Septic Blaster Powder in bucket or drum and inject into lines. Inject until all the lines have been treated. Allow contact time of 2-3 hours before repeating treatment. Flush system if possible with recirculating water.

HIGHER DOSAGE = QUICKER RESULTS

**For Systems with Grease,
Use Septic Blaster Powder to
Help Dissolve Grease & Blockage**

1 : 1500

**1 gallon of Septic Blaster Powder per
1,500 gallons of System Water**

**Inject Septic Blaster Powder
15 Minutes per Zone**

**Allow Contact 4-8 Hours
Repeat 2-3 Times**

